

AIR COOLED
DIESEL WELDER-
GENERATOR

YDW190AE

YANMAR



Photograph may show optional equipment.

For Versatile, High Performance Welder-Generator Sets, Hook Up with Yanmar!

Versatility

Yanmar's welder-generator set is in fact a rectified DC welder and a revolving field type AC generator. With its large capacity output, this unit has the versatility to handle a wide range of welding currents to suit your job.

Features

High quality welds can be achieved at low current levels. Voltage fluctuations are small driving welding. The arc is easy to keep running, giving high quality continuous welds. Because it is a multipole generator, a reactor becomes unnecessary, allowing substantial weight savings, while reducing the possibility of any trouble at an overload situation.

Economical

A "Slow down" mechanism in the dual starting version automatically lowers engine speed during breaks in welding, cutting both fuel and lube oil consumption. Combined with Yanmar's already fuel-thrifty engines, running costs are low.

Long Operation with Large Capacity Fuel Tank

A large capacity fuel tank is equipped for long hours of continuous operation. The YDW190AE delivers 15 hours of continuous welding operation (at 50%load, 50Hz) and 11 hours of continuous power generation (at rated output).

Compact and Lightweight

An efficient frame and useful weight savings. Moreover the Yanmar diesel engine powering this unit is amongst the world's marvel of miniaturization.

Low Noise, Low Vibration

The Yanmar welder generator features a large capacity exhaust muffler to reduce engine noise, and

a vibration-proof support to slash vibration and mechanical noise. The YDW190AE is ideal for jobs that require quiet.

Durable Construction

Every part is designed to ensure maximum durability for many hours of trouble-free operation. An oil pressure drop shut-off system in the

dual starting version stops the engine when lube oil pressure falls.

One-Side Control

All control devices and service points are situated on the same side for easy operation and maintenance. Simply key starting and stopping adds to the convenience in the dual starting version.




L-A SERIES AIR-COOLED DIESEL ENGINE

Its secret in the world's smallest fuel injection system

The fuel injection system, the heart of the diesel, has been refined through years of research and development at Yanmar. We have now succeeded in minimizing the weight and size and simplifying the structure by adopting a bushless pump and cutting the nozzle size.

- **Superb durability**— because it is built by a specialist in large diesel technology.
- **Instant starting by recoil starter**— the first time in an air-cooled diesel.
- **Fuel costs dip to a new low with Yanmar's direct fuel injection system.**
- **Very low vibration and quiet running.**



SPECIFICATIONS

Model		YDW190AE		
		Recoil	Dual start	
WELDER	Type	Rectifier type, DC Welder (w/Brush)		
	Rated output	4.37		
	Rated current	165		
	Current range	50-180		
	Rated voltage	26.5		
	Voltage at no-load	45-65		
	Rotation speed	3600		
	Applicable electrode	2.6-4.0 (0.10-0.16)		
AC GENERATOR	Rated of use	50		
	No. of phase	Single		
	Voltage	200/220, 220/240		
	Frequency	50/60		
	Rated output	2.3/2.7		
ENGINE	Power factor	1.0		
	Type	Single cylinder, Vertical 4-cycle, Air-cooled diesel engine		
	Model	L100AE-DW	L100AE-DEW	
	Displacement	406 (24.78)		
	Max. output/speed	10/3600		
	Starting system	Recoil	Dual (Recoil/Electric)	
	Lubricant capacity	Total ℓ (U.S. gal.)	1.65 (0.44)	
		Effective ℓ (U.S. gal.)	0.6 (0.16)	
	Fuel oil capacity	Total ℓ (U.S. gal.)	13.5 (3.57)	
		Effective ℓ (U.S. gal.)	13 (3.43)	
Emergency stop (Oil sensor)	—	Standard		
Slow-down device	—	Standard		
Frequency changeover switch	Standard			
SET	Dimensions L x W x H	720 x 510 x 632 (28.3 x 20.1 x 24.9)		
	Dry Weight	107 (236)	120 (265)	

Note: All data subject to alteration without notice.

YANMAR CO., LTD.

1-32, Chayamachi, Kita-ku, Osaka 530-8311, Japan
 Telephone: 06-6376-6411 Facsimile: 06-6377-1243
<http://www.yanmar.co.jp>